



Bioplast(er) 2K

General informations

2 component seam glue and application machine. Prevents sticking to the roller, because of the re-activ seam glue. It gets highly stable when it runs over the edge. The application machine can be cleaned easily, because the 2 components react only after they have been mixed. Individually, they do not cure.

Application areas

Gluing of seams in road construction (hot on cold asphalt)

Advantages

- Building high quality (steadily) seams with gentle manpower - **self propelled machine**
- High stable, traversable seam edge (**2K**)

Delivery form

Bioplast

package: 55 kg

component A = 25 l 30 kg


component B = 25 l 25 kg

palett: 6 packages

Storage



- no frost
- direct sun possible
- rain possible



Bioplast

2K-Naht

Technical Data

Density:	Component A: 1,11 g/cm ³ Component B: 0,98 g/cm ³
Storage time:	12 months, airtight and dry
Processing temp.:	up to 0°C outer temperature (The surface must have minimum 5°C, can be moist but not wet!)
Pot time:	Components react only after they have been mixed. Individually, they do not cure.
Curing time:	Hardens directly on the seam edge, but gets plastically again in conjunction with the hot asphalt.

product	Art.Nr.	package	VPE
Bioplast 2K	023027	55 kg	6 packages
Bioplaster	024201		1 pcs.



Edition: 04/2013

The information in this brochure is based on experience and the current state of scientific knowledge and practice. But they are not binding and it is no privacy.