



Bioplast(er) 2K

General informations

2 component seam glue and application machine. Prevents sticking to the roller, because of the re-activ seam glue. It gets highly stable when it runs over the edge. The application machine can be cleaned easily, because the 2 components react only after they have been mixed. Individually, they do not cure.

Application areas

Gluing of seams in road construction (hot on cold asphalt)

Advantages

- Building high quality (steadily) seams with gentle manpower - **self propelled machine**
- High stable, traversable seam edge (**2K**)

Delivery form

Bioplast

package: 55 kg

component A = 25 l 30 kg

component B = 25 l 25 kg

palett: 6 packages

Storage




- no frost
- direct sun possible
- rain possible

Bioplast

2K-Naht

| product | Art.Nr. | package | VPE |
|--------------|---------|---------|------------|
| Bioplast 2K | 023027 | 55 kg | 6 packages |
| Bioplast(er) | 024201 | | 1 pcs. |
| | | | |
| | | | |



Technical Data

| | |
|-------------------|--|
| Density: | Component A: 1,11 g/cm ³ Component B: 0,98 g/cm ³ |
| Storage time: | 12 months, airtight and dry |
| Processing temp.: | up to 0°C outer temperature (The surface must have minimum 5°C, can be moist but not wet!) |
| Pot time: | Components react only after they have been mixed. Individually, they do not cure. |
| Curing time: | Hardens directly on the seam edge, but gets plastically again in conjunction with the hot asphalt. |

