

# fugi-fix<sup>.de</sup>

## PAVEMENT FIXING MORTAR

## fugi-fix high resilient

### General

**fugi-fix high resilient** is a **2-component** formulation product based on epoxy resin and quartz sand.

### Typical application

- Grouting of all paving slabs in car and truck areas **up to 40 t loads**, from 8 mm joint width and 30 mm joint depth
- Particularly for heavy load areas and bus stations

Product	Colour	Art.-Nr.	Unit	P.U.
fugi-fix high resilient	sand	028013-1	28 kg	24 buckets
fugi-fix high resilient	grau	028014-1	28 kg	24 buckets
fugi-fix high resilient	anthrazit	028015-1	28 kg	24 buckets



UPDATE  
09/2018



### Features

- For highest **Trafficloads up to 40 t**
- Frost & de-icing salt resistant
- Permanent joint seal
- From **0°C substrate temperature** application possible
- Very low water permeability

### Technical specifications

<b>Composition:</b>	epoxy resin and quartz sand
<b>Colours:</b>	sand/light, grey, anthracite
<b>Density:</b>	1,74 g/cm <sup>3</sup>
<b>Compressive strength:</b>	73,0 N/mm <sup>2</sup>
<b>Flexing tensile strength:</b>	21,1 N/mm <sup>2</sup>
<b>Water permeability:</b>	0,015 l/min./m <sup>2</sup>
<b>Application temperature:</b>	0°C to +35°C

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.

## fugi-fix

c/o Nadler Straßentechnik GmbH

Fraunhoferstraße 3 | D-85301 Schweitenkirchen

Tel.: 0 84 44 - 92 400 - 0 | Fax: 92 400 - 40

E-Mail: [info@fugi-fix.de](mailto:info@fugi-fix.de) | Web: [www.fugi-fix.de](http://www.fugi-fix.de)

