

fugi-fix^{.de}

PAVEMENT FIXING MORTAR

fugi-fix ORIGINAL+

General

fugi-fix ORIGINAL+ is a 1-component acrylic dispersion and is used to set grit, sand etc.

Typical application

- Grouting for all paving slabs and tiles
- For pedestrian loads
- From 1 mm joint width
- From 20 mm joint depth for application on drainable substructures incl. bonding course

| Product | Art.-Nr. | Unit | P.U. |
|--------------------|----------|--------|--------------|
| fugi-fix ORIGINAL+ | 028030 | 1 l | 12 PE-Bottle |
| fugi-fix ORIGINAL+ | 028034 | 10 l | 1 Canister |
| fugi-fix ORIGINAL+ | 028032 | 200 l | 1 Drum |
| fugi-fix ORIGINAL+ | 028033 | 1000 l | 1 Tank |

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.

fugi-fix

c/o Nadler Straßentechnik GmbH

Features

- Approved for ceramic tiles
- Suitable for unbound designs
- Easy application
- Weed free joints
- Permanent water permeability
- Can be applied to substrate +7°C and above

Technical specifications

| | |
|---------------------------------|---------------------------------|
| Composition: | Spezial-Emulsion auf Acrylbasis |
| Colours: | colourless |
| Verarbeitungstemperatur: | +7°C bis +35°C |



UPDATE
09/2018

Fraunhoferstraße 3 | D-85301 Schweitenkirchen

Tel.: 0 84 44 - 92 400 - 0 | Fax: 92 400 - 40

E-Mail: info@fugi-fix.de | Web: www.fugi-fix.de