

## fugi-fix quick fix

### General

**fugi-fix quick fix** is a **2-component** formulation based on epoxy resin and quartz sand.

### Typical application

- Grouting of all pavingslabs in car and truck areas up to **25 t loads**
- From 5 mm joint width and 30 mm joint depth

Product	Colour	Art.-Nr.	Unit	P.U.
fugi-fix quick fix	sand	028010-1	30 kg	24 buckets
fugi-fix quick fix	grey	028011-1	30 kg	24 buckets
fugi-fix quick fix	anthracite	028012-1	30 kg	24 buckets



UPDATE  
09/2018



### Features

- **25 t load bearing after 24 hours**
- **Workable in light rain**
- **Good fluidity**
- **Frost & de-icing salt resistant**
- **Permanent joint seal**
- **Can be applied to substrate 0°C and above**
- **Permanent water permeability**

### Technical specifications

<b>Composition:</b>	epoxy resin and quartz sand
<b>Colours:</b>	sand/light, grey, anthracite
<b>Density:</b>	1,67 g/cm <sup>3</sup>
<b>Compressive strength:</b>	49,3 N/mm <sup>2</sup>
<b>Flexing tensile strength:</b>	14,6 N/mm <sup>2</sup>
<b>Water permeability:</b>	0,03 l/min./m <sup>2</sup>
<b>Application temperature:</b>	0°C to +35°C

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.

