

fugi-fix^{.de}

PAVEMENT FIXING MORTAR

fugi-fix resilient

General

fugi-fix resilient is a **2-component** formulation based on epoxy resin and quartz sand.

Typical application

- Grouting of all pavingslabs in car and truck areas up to **7.5 t loads**
- From 3 mm joint width and 30 mm joint depth
- **From 20 mm joint depth** for application on drainable substructures incl. bonding course

Product	Colour	Art.-Nr.	Unit	P.U.
fugi-fix resilient	sand	028007-1	30 kg	24 buckets
fugi-fix resilient	grey	028008-1	30 kg	24 buckets
fugi-fix resilient	anthracite	028009-1	30 kg	24 buckets

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.



UPDATE
09/2018



Features

- **Approved for ceramic tiles**
- Particularly suited to narrow joints
- Extremely good fluidity and workability
- Load-bearing up to **7.5 t**
- Permanent joint seal
- **Can be applied to substrate 0°C and above**
- Permanent water permeability
- Frost & de-icing salt resistant

Technical specifications

Composition:	epoxy resin and quartz sand
Colours:	sand/light, grey, anthracite
Density:	1,47 g/cm ³
Compressive strength:	24,5 N/mm ²
Flexing tensile strength:	7,5 N/mm ²
Water permeability:	2,3 l/min./m ²
Application temperature:	0°C to +35°C

fugi-fix

c/o Nadler Straßentechnik GmbH

Fraunhoferstraße 3 | D-85301 Schweitenkirchen

Tel.: 0 84 44 - 92 400 - 0 | Fax: 92 400 - 40

E-Mail: info@fugi-fix.de | Web: www.fugi-fix.de