

fugi-fix^{.de}

PAVEMENT FIXING MORTAR

fugi-fix slurry

General

fugi-fix slurry is a 1-component formulation based on quartz sand, liquid polybutadiene and linseed oils. The product is vacuum packed.

Typical application

- Grouting for all paving slabs in pedestrian areas
- From **5 mm joint width** and 30 mm joint depth
- From **20 mm joint depth** for application on drainable substructures incl. bonding course

Product	Colour	Art.-Nr.	Unit	P.U.
fugi-fix slurry	sand/light	028001-1	25 kg	40 buckets
fugi-fix slurry	grey	028002-1	25 kg	40 buckets
fugi-fix slurry	anthracite	028003-1	25 kg	40 buckets

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.



UPDATE
09/2018



Features

- **Approved for ceramic tiles**
- **Frost & de-icing salt resistant**
- **Ready to use, 1-component**
- **The product can be spread**
- **Permanent joint seal**
- **Permanent water permeability**
- **Can be applied to substrate +0°C and above**

Technical specifications

Composition:	quartz sand, liquid polybutadiene and linseed oils
Colours:	sand/light, grey, anthracite
Density:	1,46 g/cm ³
Compressive strength:	5,6 N/mm ²
Flexing tensile strength:	3,2 N/mm ²
Water permeability:	approx. 11 l/min./m ²
Application temperature:	0°C to +35°C

fugi-fix

c/o Nadler Straßentechnik GmbH

Fraunhoferstraße 3 | D-85301 Schweitenkirchen

Tel.: 0 84 44 - 92 400 - 0 | Fax: 92 400 - 40

E-Mail: info@fugi-fix.de | Web: www.fugi-fix.de