

fugi-fix^{.de}

PAVEMENT FIXING MORTAR

fugi-fix stonedesign

General

fugi-fix stonedesign is a 1-component grit and gravel fixative for the decoration of external surfaces of various load bearing capacities.

Typical application

- Fixing of gravel and grit in private settings
- for path laying and tree surrounds

Product	Art.-Nr.	Unit	P.U.
fugi-fix stonedesign	028016	1 kg	1 tin
fugi-fix stonedesign	028016	1 kg	10 tins

The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual legal relationship. Changes, misprints and errors reserved.



UPDATE
09/2018

Features

- For areas from 30 mm deep
- Walkable after 24 hours
- Colour-fast
- UV- and water-resistant
- Permanent joint seal
- Highly water permeable
- Frost & de-icing salt resistant

Technical specifications

Composition:	PU-Resin
Density:	1,65 g/cm
Compressive strength:	6,3 N/mm ²
Flexing tensile strength:	1,75 N/mm ²
Application temperature:	+7°C to +25°C

fugi-fix

c/o Nadler Straßentechnik GmbH

Fraunhoferstraße 3 | D-85301 Schweitenkirchen

Tel.: 0 84 44 - 92 400 - 0 | Fax: 92 400 - 40

E-Mail: info@fugi-fix.de | Web: www.fugi-fix.de