

EN

# PRODUCT**CATALOGUE**

**INTERNATIONAL VERSION** 









### NADLER STRASSENTECHNIK ABOUT US

Nadler Straßentechnik GmbH has been supplying customers in road construction and civil engineering, in municipal institutions and industry for more than 20 years. Our innovative and tried-and-tested construction materials and processing equipment are used in new road construction, road maintenance, marking and coating, manhole repair and paving.

One of Nadler's greatest strengths is that we do not just sell a product, but deliver solutions that deliver from A to Z. All of our products are subject to the strictest quality guidelines and are regularly tested to ensure they are compliant.

Since it was founded in 1998. Nadler Straßentechnik GmbH has been growing steadily and healthily. Around 80 employees now work at our innovative family business.

Our headquarters are in Schweitenkirchen, Bavaria, with a second site in Barleben near Magdeburg in Saxony-Anhalt. We have technical sales staff locally throughout Germany. Our staff visit customers in person to create tailor-made solutions to problems and present materials to our customers.


The Nadler Academy launched in 2018 as a further asset, providing practical training on all aspects of road construction. And the journey continues, as Nadler spreads across Europe with new franchise partners and new branches.

## STRASSENTECHNIK.DE









## **ASPHALTPASSION**

Nadler's ASPHALT**PASSION delivers mobility.** Expertise, service and innovative products for road maintenance, new construction and manhole frame adjustment deliver maximum mobility on all roads and motorways.

This combination makes Nadler unique in the civil engineering and road construction industry.

### **STRASSENTECHNIK'S** 7 TRUMP CARDS

- Expertise & system solutions
- Personal customer advisers
- Presentations of materials & training
- 24h delivery of fresh products
- Delivery direct to the construction site
- Well rounded product range

Recyclable product packaging

### THE FUTURE IS SOLVENT-FREE

Bavaria has a target of becoming climate-neutral by 2040 at the latest and reducing CO2 by 65% by 2030 compared to 1990. We are committed to these principles and have started by setting up a programme for climate action and sustainability.

Nadler is setting a further milestone on the path to neutrality with the introduction of the new 100 series.

"THE FUTURE IS SOLVENT-FREE" is the motto for our 100% solvent-free products.

### CONTENTS


PAGE

	ROAD MAINTENANCE	04
	ROAD CONSTRUCTION	10
	MANHOLE REPAIR	16

LANDSCAPE & PAVING WORK 20 **QUANTITY CALCULATOR** 

### SYMBOLS/MEANING







No frost

Frost tolerant

No direct sun

Sun tolerant

No rain

Rain tolerant



Giscode RepA 10

- · Label certifying products as solvent-free
- No health hazards for workers







Shelf life

### **ROAD MAINTENANCE**

POTHOLE REPAIR



### THE FUTURE IS **SOLVENT-FREE**

FOR MORE INFORMATION, GO TO: STRASSENTECHNIK.DE/100

Art. Nr.

014602-1

014603-1

014608-1

014611-1

014203



### Biophalt® 100 Solvent-free, highly stable reactive asphalt made

from renewable raw materials

Can be processed cold, fully curing

Grit size

0/2

0/5

0/8

0/11

Biophalt priming spray- primer

Can be hot overlaid

PPLICATION	
Permanent repair of bore	h

Pack

25 kg

25 kg

25 kg

25 kg

750 ml

APPLICATION

APPLICATION

holes, potholes, cracks, defects, drill core closure, ramps, etc.; for asphalt and concrete



PU	SERVICE MARK
32 buckets	To Authority St. T. F.
32 buckets	
32 buckets	DOM: No.
32 buckets	SWEET BOOK
12 tins	
	Company of the second



### Granuphalt® 100

Solvent-free, stable asphalt granulate, free-flow ing, with dry texture

- Can be processed cold, extremely strong grit bonding
- Compaction by traffic

1	<ul> <li>Permanent repair of potholes, frost cracks</li> </ul>
	and defects in asphalt bonds.
3	
1	







Temporary repairs of potholes, cracks, etc.For asphalt and concrete



### Ecophalt® 100

Solvent-free repair asphalt for cost-effective and fast repairs

- Can be processed cold
- Fast & cost-effective

. 431 41 4031 4441.74				
Product		Art. Nr.	Pack	PU
Ecophalt® 0/5 bucket	NEW	014665-1	20 kg	24 buckets
Ecophalt® 0/5 bag	NEW	014668-1	20 kg	40 bags
Manual compressor		026001		1 pc






### Pothole Repair Primer

To improve the layer bond between existing asphalt or concrete and cold mix

Optimum laver bonding

Gun for primer spray


Adhesive priming spray - primer



PU

12 tins

12 tins



Can also be used in winter

750 ml

600 ml





### **ROAD MAINTENANCE**

PRIMER - POTHOLE REPAIR/HEIGHT ADJUSTMENT/DEPRESSION









### Liquid asphalt HD (2-component)

Resin-based levelling compound

- Especially for heavy duty surfaces
- Highly resilient, abrasion-resistant & durable grip
- Fast re-opening for traffic

### APPLICATION

Levelling of depressions and rutsHeight adjustment e.g. of manholes

For asphalt and concrete

gs kets	
cet	
net	
g	

6					
ĝ	Product		Art. Nr.	Pack	PU
a	Liquid asphalt HD powder	NEW	011050	15 kg	50 bags
ä	Liquid asphalt HD curing agent	NEW	011051	3 kg	50 buckets
8					
9	Concrete primer		011036	2 kg	1 bucket
8	Catalyst		011026	100 g	1 sachet
ã	Filler QS 2/8		011053	25 kg	1 bag
83					






### Liquid asphalt - coverboard

Optimum manhole adjustment results

· Help to adjust height of manholes on installation

1 pc







014203

014022-1

014210





### **ROAD MAINTENANCE**

HEIGHT ADJUSTMENT/DEPRESSION/ROUGH ASPHALT









### Bücofix SRV (2-component

Repair and bonding PMMA-based mortar the most demanding requirements.

Art. Nr.

011011

011012

011026

011036

- · Highly mechanically resilient
- Extreme adhesion

Bücofix black

Bücofix grey

Concrete primer

Catalyst

<ul> <li>Height levelling of road paving com</li> </ul>
<ul> <li>Levelling of ramps</li> </ul>
<ul> <li>Bonding surface lighting</li> </ul>

APPLICATION


5 kg

100 g

2 |

APPLICATION












### Elasto Rep (2-component)

Solvent-free acrylate-based coating

Consistency can be adjusted with fillers



t			l



and concrete surfaces

duct	Art. Nr.	Pack	PU	
sto Rep	011015-1	7 kg	39 pack	
tive primer	011017	1	1 tin	K
ring agent	011016	80 g	1 sachet	
				William .
tallation heights: up to 2 cr	n (on surface)   up to	4 cm (poured as	phalt gutters)	1

Art. Nr.

012010






### Bitumen slurries

Ready-to-use bitumen slurries with fine mineral

Solvent free

APPLICATION · Binder enrichment of rough, deteriorated asphalt surfaces



Pack

30 kg

APPLICATION

Crack repair

3 mm












### Pattern crack repair compounds

Specially developed, solvent-free, polymer-modified bitumen emulsions

Runs down to the bottom of the crack



contains solvent 012017-1



## Biolast 2K cold grout (2-component

Cold grout compound consisting of reactive bitumen and reactive components

- · Optimum for small grouting jobs
- Excellent flank adhesion

### APPLICATION

Filling cracks and joints larger than 2 mm

in asphalt and concrete

Casting induction loops, etc.

V	200	26	022	86
1	REAL PROPERTY.		100	
			80%	
300	ALG:	May 1		

Product	Art. Nr.	Pack	PU
Biolast starter pack with cortridge gun	013271	425 g	2 cartridges
Biolast Minipack	013272	425 g	12 cartridges
Biolast single cartridge	013278	425 g	1 cartridge
Biolast cartridge gun	013281		1 pc
Biolast XL	013290-1	5 l	1 bucket
OMNI primer spray - primer	021973	600 ml	6 tins
<u> </u>	·		· · · · · · · · · · · · · · · · · · ·

Art. Nr.

016112

016113

016114

016070

0160-71/73



### Kerb stone mortar (2-compone

Particularly fine-grained 2-component mortar based on epoxy resin

· Especially for repairing damage in concrete

FixBeton 2-component starter set 013220

walls and kerb stones

Pack

8 kg

20 kg

25 kg

1 kg

2 / 10 kg

9 kg

APPLICATION

Modelling for concrete or granite stairs, Repair of circular flow systems

1 bucket

1 bucket


1 bag

1 sachet

1 bucket

(e.g. in sewage treatment plants) PU

	199	
100	A COUNTY OF	į
2/	A STATE OF THE STA	Ì
1000	A STATE OF THE STA	٩
		ž



### Promatic TITAN (with piezo ignition)

8 kg Kerb stone Mortar (FB 0-1)

20 kg Kerb stone Mortar (FB 0-1)

25 kg Kerb stone Mortar (FB 0-1)

With bayonet fitting for quick burner change and with 360°-rotatable hose connection

Extremely light

Bonding agent

Bonding agent

ON/OFF function in the handle - for greater safety

### APPLICATION

Repairing asphalt surfaces

Installing waterstops
Burning on thermoplastics

Heating reinforcement sheets, etc.

Art. Nr. PU 013957 Promatic titanium manual gas burner 1 pc 5 m HP hose set 013357 7 1 pc 10 m HP hose set 013357 6 1 pc Various attachment/accessory parts On request





### GranuGrip

Highly abrasion-resistant aggregate

With visual effect

Does not sink - lighter than grout

### Spreader DS

Spreading trolley for applying skid resistant material

· Uniform spread pattern

· Width & quantity can be smoothly adjusted









### **ROAD MAINTENANCE**

CRACK & JOINT REPAIR (HOT)











### Hot grouting compounds (1-comp

Based on polymer-modified bitumen and mineral aggregates

 According to TL-Fug StB 15 and DIN EN 14188 type N2 (except for paving grout)



· Grouting joints and cracks in asphalt and concrete surfaces

· Grouting tracks and paved surfaces Sealing sheet pile locks



e NE (except for paving grout)	<u>'</u>		•
ct	Pack	Art. Nr.	PU
er joint sealant N2	0.7 kg	013101	24 blocks
er joint sealant N2	11 kg	013133	80 blocks
er joint sealant N2	30 kg	013140_1	33 buckets
g grouting (D: 1.5 g/cm³)	15 kg	013135	60 blocks
Sealant	11 kg	013163	80 blocks
primer	10/30 l	013604/05	1 canister



### Risseboy hot-air lance

Multiprimer

Hot air lance with gas cylinder holder, stone chip protection and connections

For external compressor

APPLICATION

· Cleaning and preparation of joints and cracks in asphalt and concrete surfaces

ä	Product		Art. Nr.	Weight
	Asphalt Risseboy 2021 NEW	for external compressor	013375	30 kg
	- Solo support wheel		013375-1	
	- TWIN support wheel		013375-2	
	- Side blower module		013375-3	





### KOMP hot-air lances

Hot-air lances, stone chip protection and connec-

- With integrated compressor
- Alternatively with driving assistance

APPLICATION
-------------

· Cleaning and preparation of joints and cracks in asphalt and concrete surfaces

Product Art. Nr. Weight  KOMP Mini with integr. compressor 013396 80 kg  KOMP SL with integr. compressor 013397 165 kg  - Driving assistance/LED set					
KOMP SL with integr. compressor 013397 165 kg	Product		Art. Nr.	Weight	
ů i	KOMP Mini	with integr. compressor	013396	80 kg	
ů i					E
- Driving assistance/LED set	KOMP SL	with integr. compressor	013397	165 kg	
	- Driving assistance/LED set				В
					В
					ü





### Tornado

Joint dryer with high-performance turbine

Fast and pore-deep drying or cleaning

Drying and cleaning concrete & asphalt surfaces

Marking removal







ombi-kettle with integrated mixer. ndirect heat source via heat shield; hot air distrioution via heat conduction plates.

Alternatively with temperature control

### APPLICATION

- · Grouting joints and cracks in asphalt, concrete and paved
- With integrated thermometer and hand mixer

Product	Art. Nr.	Model	Weight
KK 50 (alternatively stationary) - Also for rent	013392(2)	50 I	65 kg
KK 30	013391(2)	30 I	60 kg
Set of smooth running castors			
Grouting tools (hand puller+trowel)	013387		
Pouring can	013318	3.5	
ZSK-grouting funnel	013380	7 I	approx. 18 kg
Grout block tongs	0133871		
	,		





### Grout kettle, large

Indirectly heated large kettle with mixer

- With self-drive and pump system
- Thermostat-controlled safety cut-out
- Heated hose

### APPLICATION

• Grouting joints and cracks in asphalt and concrete surfaces

Product	Model	Art. Nr.	
R. Rupprecht Grouting kettle	120 l to 230 l	-/-	
Linnhoff Grouting kettle	300 l to 700 l	-/-	
Stationary kettle	90	0133924	
Stationary kettle	120		
Stationary kettle	120 I with pump syst	tem	
	,	100	



### RFF-A Crack & joint routing machine

Dust-free joint cutting

With built-in extraction device

HRF-L Hydraulic crack router

Hydraulic multifunctional device · Joint production after asphalt work

Routing cracks

· Removing old joint fillings

Product	Art. Nr.	Weight
Crack & joint routing machine RFF-A	013495	260 kg
Hydraulic crack router HRF-L	013365	650 kg



### PE cord (inlay cord)

Closed-cell polyethylene foam round cord, especially for grouting joints

· 2 options available

+80°C (cold grouting) +200°C (hot grouting)

	_
APPLICATION	

• Backfilling joints for hot and cold grouting

Prevents 3-flank adhesion in concrete

+ 80°C + 200°C PE cord Ø 10 mm 013149 013701 1700 m PE cord Ø 13 mm 013702 1100 m -/-1 roll PE cord Ø 15 mm 013150 013703 780 m 1 roll PE cord Ø 19 mm 013704 500 m -/-1 roll PE cord Ø 22 mm 013151 013705 360 m 1 roll PE cord Ø 25 mm 013152 013706 280 m 1 roll PE cord Ø 32 mm 013153 013707 190 m













1 roll

### **ROAD CONSTRUCTION**

CONNECTIONS IN ASPHALT & CONCRETE AREAS



EDGE SEALING/CRACK BRIDGING/STRESS RELIEF







### Joint Tape FB (in accordance with ZTV Fug-StB 15)

Weight

30 x 8

35 x 8

40 x 8

30 x 10

35 x 10

40 x 10

Fusible joint tape (special sizes on request)

Product

Joint Tape FB

FB primer

### APPLICATION

- · Permanently elastic sealing of connections in asphalt surfaces
- Joint creation for connections to paving components, etc.





APPLICATION

ing components, etc.




### Joint Tape TA (ZTV Fug-StB 15)

- Revolutionary joint tape
- Thermally activatable
- Makes primer superfluous

Product	Weight	Art. Nr.	Pack	PU
Joint Tape TA	30 x 8	021953	48 m	30 box
Joint Tape TA	35 x 8	021954	48 m	30 box
Joint Tape TA	40 x 8	021955	36 m	30 box
Joint Tape TA	30 x 10	021956	40 m	30 box
Joint Tape TA	35 x 10	021957	40 m	30 box
Joint Tape TA	40 x 10	021958	30 m	30 box







Weight

30 x 8

35 x 8

40 x 8

30 x 10

35 x 10

40 x 10

40 x 10





### Joint Tape SK & SK Yeti (ZTV Fug-StB 15)

- Self-adhesive joint tape
- Strongly adhesive special bitumen layer
- No melting-on

Joint Tape SK

SK nrimer

Joint Tape SK Yeti NEW

Product Joint Tape SK

### APPLICATION

Pack

48 m

48 m

36 m

40 m

40 m

30 m

30 m

5 I

Art. Nr.

021912

021913

021914

021915

021916

021917

021987

021934

• Permanently elastic sealing of connections in asphalt surfaces

Permanently elastic sealing of connections in asphalt surfaces

· Joint creation for connections to pav-

· Joint creation for connections to pav-

PU

30 box

90 tins


ing components, etc.

٠١٨١٠ ه



### Joint Tape OMNI (ZTV Fug-StB 15)

- Self-adhesive joint tape with unique special profile
- One size for all top layer thicknesses
- APPLICATION Permanently elastic sealing of connections in asphalt surfaces
- Joint creation for connections to paving components, etc.









### ElastoRand edge sealant (1-comp

Polymer-modified bitumen emulsion for edge sealing of the asphalt surface (according to TL S-Bit 15)

Solvent-free

ElastoRand

Can be processed cold

Elasto-Mat - standard

Elasto-Mat - edge module

AP	PLIC	ATIC	N

Pack

30 kg

APPLICATION

Art. Nr.

023031-1

024108

024121

Available to ren

Preferably cold sprayed with the Elasto-Mat-Edge module.

PU

18 buckets

Production of flexible and durable

seams for sheet installation of rolled

18 buckets







A language	
and the same of	
	氢
	12
	33
	霊
	褞



### ElastoPlast seam adhesive (1-comp

Stable bitumen compound for highly flexible and durable seam connection (according to TL S-Bit 15)

<ul><li>Solvent-free</li><li>Can be processed cold</li></ul>		asphalt ("ho	ot to cold").
Product	Art. Nr.	Pack	PU
ElastoPlast	023017-1	25 l	18 buck
Elasto-Mat - standard	024108		
Elasto-Mat - seam module	024122	200	
	Available to rent	t! 🐠 💮	
		201	













### Joint impression wheel (Lightning joint system)

Creates an even joint gap for a high-quality

Fast and efficient     Can be combined with existing		
Product	Model	Art. Nr.
Joint impression wheel up to 1.5 t	Cat. I	013490
Joint impression wheel up to 3.5 t	Cat. II	013491
Joint impression wheel from 3.5 t	Cat. III	013492




### APPLICATION


APPLICATION

Production of a joint gap in the transition area from new to old for subsequent hot grouting

· Joint production at connections, kerbs and paving elements







### Joint positioning Tape

Revolutionises the positioning of joints in rolled asphalt surfaces

- Can be pulled out after the asphalt has been laid
- Clean joint production

Product	Model	Art. Nr.	PU
Joint positioning Tape	40 x 15 mm	013166	250 running metre
Joint positioning Tape SK	40 x 15 mm	013167	250 running metre
Joint positioning Tape	50 x 20 mm	013168	150 running metre







on rolled asphalt construction sites









## **ROAD CONSTRUCTION**

RELEASING AGENT/CLEANING/ACCESSORIES











### Asphalt releasing agent PMB

Releasing agent concentrate based on raw plant materials. Excellent releasing effect

- Water dilutable 1:6
- Solvent-free & biodegradable



APPLICATION

200 l

1000 I

APPLICATION

· Road rollers, rubber wheeled rollers, pavers, truck beds, mixing plants, tools











### Asphalt releasing agent **PUR**

Mineral oil-based releasing agent with excellent & long-lasting releasing effect

Asphalt release agent PUR mineral oil based

Asphalt release agent PUR mineral oil based

Asphalt release agent PUR mineral oil based

Particularly suitable for Thermo containers

		ot galvanised tanks iixing plants, tools	
Art. Nr.	Pack	PU	
022131	20 I	30 canister	

· Road rollers, rubber wheeled rollers,

1 drum

1 IBC

Asphalt retention samples at asphalt construction sites





### Asphalt sample bucket

Retention sample buckets for asphalt according to TP Asphalt-StB, Part 27.

- With press-in lid & top hinged handle
- Including heat-resistant info sticker


oduct	Art. Nr.	Pack	PU	
sphalt sample bucket	022060	10 l	250 buckets	100
				100

022024-1

022132

022133





### B-EX bitumen cleaner

Ready-to-use emulsion cleaner and degreaser with very high solvency

Dries without residue or streaks



500 ml

12 tins

APPLICATION







Bitumen emulsion consisting of road construction bitumen, water, emulsifiers and solvents.

Can be processed cold

Adhesive emulsion



· For bonding individual asphalt layers in accordance with TL BE-StB 15, ZTV-Asphalt StB 07/13.









### HKS Pro adhesive sprayer

Optimal for small construction sites in combination with our 20 kg small adhesive containers

Eliminates the need for manual distribution

Efficient and fast distribution of bituminous adhesives and releasing agents

Product	Art. Nr.	Model	PU
HKS Pro	024079	18 l	1 pc
HGV-Adapter 2 m hose	024082		1 pc
Valve adapter	024083	brass	1 pc
Hand Lance for HKS Pro	024089		1 pc
Fan nozzle 110° blue	024081	plastic	1 pc
Spare spiral hose	024091	5 m	1 pc





### Spraying machines

Spritzmaus machines and self-propelled machines and attachments for spraying bitumen emulsions (according to TL BE-StB 15)

• Tank volume up to 12000 l

### APPLICATION

For edge sealing, seam treatment and spraying work
 Also suitable for C 60 BP4-S

Maus spraying machine MS 80AH Petrol/diesel engine - Other Maus machines on request -Edge sealing, seam treatment TM 600 G Attachment for pre-spraying, 600 I tank HK 1000 (tank volume from 1000 l Surface-mounted device for pre-spraying, edge sealing and seam treatment to 12000 I) - Other self-propelled spraying machines on request -





### SCHAP & SCHAP box manhole cover plates

SCHAP: Made of steel with welded-on cross bracing

SCHAP box: Safety/storage system for 12 SCHAPs, fully galvanised, stackable

### APPLICATION

• Drive-over protection for vehicles and people and protection


of the component from internal contamination

Compact transport & storage system













### **ROAD CONSTRUCTION**

ASPHALT TRANSPORT & DISTRIBUTOR



ASPHALT TRANSPORT & DISTRIBUTOR









## amtec ASPHALT**BOX**

The asphalt Thermocontainer are manufactured using a stable lightweight construction. This allows for high payloads and large volume reserves during filling.

All attachments are galvanised. Weatherproof lid closures prevent water penetration and cooling of the hot asphalt during operation.

### FEATURES

- Particularly light and stable
  Different rear designs for ease of uncoupling
  Cover opening using gas pressure spring/hydraulics
- 2-chamber version
- Support feet, crane lugs or forklift pockets
- · Safety operating system



### amtec TWINBOX 4D halt Thermocontainer made of Hardox

The perfect asphalt Thermocontainer for repair work and paver loading.

Newly developed corrosion and condensation protection extends the service life many times over and maintains a durable insulating performance.

### FEATURES

- Stainless steel outer shell
- Durable due to Hardox quality and use of highstrength steels
- Economical due to low dead weight and high payload
  Perfect insulation and condensation protection
- Maximum filling opening despite low design
- Safety operating system
- Corrosion protection





PAGE 14

### amtec SIDE DISTRIBUTOR ASV For asphalt & shoulder laying

The side distributor is an attachment for wheel loaders and municipal vehicles.

Can be used for hard shoulder laying (bulk material) and for asphalting pavements and pipe trenches.

### FEATURES

- · High output rate Labour savings
- · Reduces manual installation



## HARDOX THERMOCONTAINER

The robust CMT Asphalt Thermocontainer with Hardox are tailored to customer requirements and

The stable and particularly lightweight container offers high payloads for asphalt and bulk material. Models are available as roll-off or tipper bodies with different rear designs with manual operation, hydraulic or pneumatic.

### **FEATURES**

- Particularly light and stable
- Perfect insulation and condensation protection
- Use for hot asphalt and bulk material
- · Hardox inner container
- Stainless steel outer wall
- Safety operating system
- Corrosion protection



### amtec ASPHALT DISTRIBUTOR Hydraulic asphalt unloade

Optimal for feeding foot path layers and for distributing asphalt in pipe and cable trenches.

With the radio-controlled conveying arm, the exact amount of asphalt needed can be supplied for laying.

### **FEATURES**

- · High degree of safety
- Significant labour savings
- Can be retrofitted to existing asphalt containers.
- As an attachment, can be flexibly upgraded



### amtec ASPHALT CONVEYOR BELT Hydraulic attachment conveyor belt

Hydraulic add-on conveyor for tipper bodies and asphalt thermo containers.

Optimal for unloading asphalt at paving sites next to the lane and for side filling the road shoulder.

### FEATURES

- · Even, accurate and fast material discharge.
- Adapters for different attachment solutions
- · Easy to clean
- Safe to use in the tipping area
- Significant labour savings







· Fold up when driving

### **MANHOLE REPAIR**

FORMWORK/INSTALLATION TOOLS/REPAIR PRODUCTS









### **Grouting Moulds**

Moulds for grouting mortar in various designs

• Grouting annular gaps during manhole frame adjustment







### Dirt collecting tray SAT

Made of aluminium with rubber rim

• Prevents excavated material and grout residue from falling into the manhole structure during manhole repair.

Product	Art. Nr.	Model	Weight
Dirt collecting tray SAT	032001	aluminium	7.5 kg
Replacement rubber SAT	032001 1		





### Riser Rings / Rubber Spacer

Concrete riser rings (outer diameter smaller than that of the manhole frame)

Rubber spacer made of hard rubber

APPLI	CAT	ION

· Riser rings are placed and set into the manhole with rubber

• System for manhole repair

		-	
Product	Model	Art. Nr.	PU
Riser ring	3 cm	030013	1 pc
Riser ring	5 cm	030015	1 pc
Riser ring	8 cm	030018	1 pc
Rubber spacer	1 m piece	030010	1 pc





PAGE 16

### Adjustment device JVR

For the free-hanging installation of manhole frames without wedges or similar.

3 adjustable feet, can also be used next

to kerb stories	
Product	Art. Nr.
Adjustment device JVR	032210



· Adjusting manhole frames to road level





### lanhole Frame Lifter

Fully hydraulic manhole frame lifter for all frame adjustment applications

With a lifting capacity of 34 t

top layer	gn the asphalt		
Product	Art. Nr.	Model	Weight
Manhole frame lifter 4.3	032497	Motor hydraulics	360 kg
Cutting ring - class D	032425	centring	
Adapter ring Ø up to 880 mm	032483		



Lifting manhole frames during new construction or manhole



### Manhole Frame Lifter

Fully hydraulic manhole frame lifter

• With a lifting capacity of 33 t

With height stop - automatic adjustment of the expanding bit to the height of the annular gap

Art. Nr. Manhole frame lifter 3.3 NEW 032493 Motor hydraulics 290 kg

Adapter ring Ø up to 880 mm 032483





### anhole Frame Lifter

Manual hydraulic manhole frame lifter

With a lifting capacity of 33 t

 With height stop - automatic adjustment of the expanding bit to the height of the annular gap

APPLICATION

APPLICATION


APPLICATION

repair

• Lifting class D and B manhole frames during repair

• Lifting class D and B manhole frames during repair

Art. Nr Manhole frame lifter 3.1 032492 Manual hydraulics



## **MANHOLE REPAIR**

TOOLS/REPAIR PRODUCTS











Made from biological reactive bitumen

- Long-lasting damping properties Fits in ALL manhole covers

EPDM damping ring, black

and surface box covers			
Product	Art. Nr.	Model	PU
Anti-rattle pads	031224	50 рс	1 box
Anti-rattle pads pack of 4 NEW	904008	4 pc	1 pc
Nadler spray adhesive	031225	200 ml	12 tin
Damping ring, black	031203	DIN 4290	100 pc
Damping ring, grey	031204	DIN 19584	100 pc
EPDM damping ring, black	031222	DIN 4290	100 рс

031223

APPLICATION

DIN 19584

Prevents manhole covers from rattlingProtects the cover support surface





### APPLICATION

Class D400 cover with just 10 cm height

Replacement of manhole cover to be repair because of insufficient clearance between cone and street level (< 16 cm)</li>

100 pc

Product	Art. Nr.	PU
Frame without cover with concrete	031414	10 рс
Cover with ventilation and concrete	031415	10 pc
Cover without ventilation with concrete	031416	10 pc
Cover, 16-hole	031426	10 pc
Dirt tray	031409	10 pc





### **Manhole Cover Lifting Trolley**

Mobile manhole cover lifter

• Opening and moving manhole covers

APPLICATION

Product	Art. Nr.	Model	Weight
MSD Flexi	032120	telescopic	12 kg
Various hooks	On request		





### Manhole Cover Lifter

Manhole cover lifter made of aluminium or steel

• Opening manhole covers, sliders and hydrants Including blocked covers, using the manual hook

Product	Art. Nr.	Model		Weight
Titan Alu	032101		for manholes, caps	3 kg
Claw tool, standard	032153	80 cm	or fixed covers, sliders,	2 kg
			caps and manhole	
Claw tool, long	032153-1	95 cm	covers	2 kg





Made of steel with special hook for sludge bucket

Available in two different lengths

APPLICATION

Opening sink boxes

Product	Art. Nr.	Model	Weight
Hebefix, standard	032117_2	70 cm	3 kg
Hebefix, long	032117_3	80 cm	3 kg





### NADLER Measuring Jug

For quality assurance when processing manhole mortar and liquid asphalt

With a special measuring scale for litres

and kilograms

Measures quantity of water required and kilogram value measured for dividing containers

Product	Art. Nr.	Model	PU
NADLER measuring jug	032036	5 l	1 pc





### Mixers

Single and double shafted hand mixers

APPLICATION

• For mixing grout and manhole mortar etc.

Product	Art. Nr.	Model	Weight
CX X01 (HF)	032043	680 rpm.	5.3 kg
Spare paddle	032054	right spiral	
Spare paddle CX 10	032055	left spiral	
Spare paddle CX X01	032058	left spiral	
Double shaft	- on request -		
CX X10 NC (cable free, with battery)	032043-1	640 rpm.	5.5 kg





### Accessories

 $Grouting\ buckets, compressed\ air\ compressors, etc.$ 

 Special grouting bucket for 1 complete bag of grouting/ manhole construction mortar with pouring lip

• Mini compressor for grouting moulds

Product	Art. Nr.	Model	PU
PE-grouting bucket	032033	30 I	1 pc
Rapidon	051070	61	1 pc
Mini-compressor	0320024	8 bar	1 pc
Tyre inflator with 5m spiral hose	0320043		1 pc









### LANDSCAPE & PAVING WORK

PAVING GROUT (BONDED CONSTRUCTION)





### LANDSCAPE & PAVING WORK

PAVING GROUT (BONDED CONSTRUCTION)







### fugi-fix Original+ (1-component)

Specialised dispersion for hardening grouting (e.g.: quartz sand)

Also for use in unbonded laying

Product	Art. Nr.	Pack	PU
fugi-fix Original+	028030	1	12 bottl
•			

Art. Nr.

028001-1

028002-1

028003-1

Art. Nr.

028007-1

028008-1

028009-1

Z0280

Art. Nr

028017

028018

028019

sand

grey

anthracite

Coloui

sand

grey

anthracite

div.

grey

anthracite







### fugi-fix slurry (1-component)

Based on linseed oils, polybutadine and quartz sand

For pedestrian loads

fugi-fix slurry

fugi-fix slurry

Grouting for all paving slabs in pedestrian


APPLICATION

• From 3 mm joint width & 30 mm joint depth









· Consolidation of joint filling materials

From 1 mm joint width & 30 mm joint depth

in paved pedestrian areas





### fugi-fix resilient (2-component)

Based on epoxy resin and quartz sand

For loads up to 7.5 t



Pack

30 kg

30 kg

30 kg

27.5 kg


Pack

25 kg

25 kg

25 kg

 Grouting of all paving slabs in car and truck areas up to 7.5 t load • From 3 mm joint width & 30 mm joint depth



PU

24 buckets

24 buckets

24 buckets

24 buckets









### fugi-fix reno (2-compo

Based on epoxy resin and quartz sand

For loads up to 25 t

fugi-fix reno NEW

fugi-fix reno NEW

fugi-fix reno NEW



30 kg

30 kg

30 kg

for loads of up to 25 t

From 3 mm joint width & 10 mm joint depth

24 buckets

24 buckets

24 buckets





Repair of old paving and channels for defective/broken cement joints



### fugi-fix quick fix (2-component)

Based on epoxy resin and quartz sand

For loads up to 25 t

### APPLICATION

Pack

30 kg


30 kg

30 kg

 Grouting of all paving slabs in car and truck areas up to 25 t loads

From 5 mm joint width & 30 mm joint depth





Colour

grey

anthracite

sand

grey

Art. Nr

028010-1

028011-1

028012-1

Art. Nr.

028013-1

028014-1

028015-1

### APPLICATION

Pack

28 kg

28 kg

28 kg

Grouting of all paving slabs in car and truck areas up to 40 t loads

• From 8 mm joint width & 30 mm joint depth

24 buckets

24 buckets

24 buckets









### fugi-fix **stone design**

Gravel and grit stabiliser for the decorative

design of exterior surfaces

### APPLICATION

Suitable for the production of stone carpets

Grouting of paved surfaces in pedestrian areas.



Art. Nr. Pack PU 028016 1 I 1 tin






### IBC high-pressure cleaner

Pavement joint cleaner, compressor-driven

### APPLICATION

Joint cleaning of paved surfaces

Many other possible applications






**PAGE 21** 


















PAGE 22






### YOU CAN ALSO USE OUR **QUANTITY CALCULATOR** CONVENIENTLY ON **STRASSENTECHNIK.DE**







### **EVEN MORE FROM NADLER?**

### FOLLOW US ON...

















The information printed in this brochure is based on experience, current research and practice, it is non-binding and does not establish a contractual relationship. Changes, misprints and errors reserved.



### NADLER STRASSENTECHNIK GMBH

FRAUNHOFERSTRASSE 3 D-85301 SCHWEITENKIRCHEN GERMANY/ALLEMAGNE

- +49 178 77 99 261
- +49 84 44 92 400 60
- EXPORT @ STRASSENTECHNIK.DE



# STRASSENTECHNIK.DE





O INSTAGRAM



YOUTUBE



in LinkedIN